

Publication Number: 02284125 A

Date of Publication: 1990.11.21

Int.Class: G02F 1/167

Date of Filing: 1989.04.26

Applicant: NIPPON MEKTRON LTD
 Inventor: OSHIRO TATSUHIKO
 TOYAMA JIRO
 AKATSUKA TAKATOSHI
 TADAKUMA AKIRA
 MORI TAKASHI
 ELECTROPHORETIC DISPLAY DEVICE
 AND PRODUCTION THEREOF

Abstract

PURPOSE: To easily and surely inject a dispersion system into the respective pores of porous spacers by providing hot-melt adhesive layers which can be thermocompression bonded in the circumferential regions of the spacers and forming one of electrode plates flexible.

CONSTITUTION: The dispersion system 7 dispersed with electrophoresis particles 6 is excessively supplied to the porous spacers 8 packaged on an electrode pattern 2 side of the rigid electrode plate and thereafter, the flexible electrode is disposed on the spacers 8 in such a manner that the electrode patterns 4 thereof face the electrode patterns 2 of the rigid electrode plate. The hot-melt adhesive layers 9 provided around the spacers 8 and the flexible electrode plate 4 are thermocompression bonded while the excess dispersion system 7 is extruded out by pressing the front surface of the flexible electrode plate 4 under heating to seal the dispersion system 7 into the respective pores 8A of the spacers 8. The sure injecting treatment and sealing treatment of the dispersion system 7 are rapidly executed in this way.

COPYRIGHT: (C)1990,JPO & Japio

